Roof Lantern Roof Lantern Pyramid

TB432

Skyseal Roof Lantern Datasheet

Product Description

Skyseal Roof Lantern is an elegant double-glazed glass rooflight, with a fully thermally broken and powder coated aluminium frame. It is intended for quick and easy installation on flat roofs of all modern building types to provide natural light, and is manufactured to ISO 9001 industry standards.

Design Features



- Stylish glass rooflight with slender aluminium frame offering clean sight lines and neat junctions
- Designed for rapid installation with no silicone sealant other than to seal between roof and rooflight
- Toughened inner and outer pane as standard with optional laminated inner pane for enhanced overhead safety as recommended by the Rooflight Association.
- Highly thermally efficient with thermally broken frame and Low-E double glazing
- 10 year warranty available
- Choice of clear/clear neutral self-clean or blue solar-control self clean glass as standard
- Special glass options also available
- 4 panes of glass as standard for a contemporary look, with the option of 6 panes for a more traditional aesthetic or where site access is limited
- Aluminium frame powder coated internally and externally in combinations of RAL 7016 grey, RAL9010 white and RAL 9005 black
- Designed for simple mounting direct to a weathered builder's upstand

Composition

The double glazed glass panel is made up of: 4mm toughened outer, a 90% argon filled cavity, with either a 4mm toughened inner or optional 6.8mm laminated inner (including PVB interlayer). All double glazed units include a soft coat Low E coating.

The frame incorporates aluminium extrusions and castings, un-plasticised rigid PVC extrusions, ABS and rubber mouldings, and stainless steel fasteners.

All aluminium is powder coated internally and externally in combinations of RAL 7016 grey, RAL 9010 white and RAL 9005 black to provide a premium appearance and highly appealing finish.

The Glass, Aluminium, PVC, ABS, EPDM rubber and stainless steel which comprise the product can be recycled at the end of useful product life.

Durability

Skyseal Roof Lantern units are expected to remain fit for purpose in normal conditions for a period of 20 years (with a warranty available providing a 10 year guarantee) i.e. they will not become perforated, lose significant structural integrity, or distort to the extent of losing weather-tightness. The available warranty also guarantees insulated glass used in the construction of the rooflight for 5 years.

Safety Requirements and CDM

These rooflights should beconsidered FRAGILE. It is the customer's responsibility to ensure a risk assessment has been carried out to define the measures required to prevent significant risk of falling through the rooflight, in compliance with the CDM regulations. For further information please see Rooflight Association NTD14.

Available with double glazing incorporating an inner pane that is either 1) annealed laminated or 2) toughened.

TECHNICAL SUPPORT: For any technical information/queries please contact your supplier.

Skyseal operates a policy of continuous product improvement, and reserves the right to alter specifications at any time without notice. Every effort has been taken to ensure all details contained in this document are correct at the time of going to press but this document should be used only as a guide and does not in any way form part of a contract or warranty. It is the customer's responsibility to ensure that the product is suitable for the actual conditions of use, which are beyond the control of Skyseal.

Roof Lantern Roof Lantern Pyramid

TB432
Skyseal Roof Lantern Datasheet

Safety Requirements and CDM continued

Annealed laminated inner pane
An annealed laminated inner pane prevents falling glass in the event of accidental breakage, for the safety of those below the rooflight. In some circumstances, annealed, laminated glass can be subject to thermal stress fracture in the event of uneven heat build-up directly under the glass. Installation of blinds, or any other alterations made to the lightwell below the rooflight, must be done so with consideration to the risk of thermal stress fracture. In the case of blinds, the risk of thermal stress fracture can never be fully removed, but it can be reduced by choosing light coloured blinds and positioning them as far away from the glass as possible. More detailed guidance can be obtained upon request.

Toughened inner pane
British Standards set out the circumstances and locations when a toughened inner pane can be used, subject to satisfactory risk assessment. The Rooflight Association recommends that the inner pane should always be laminated glass, unless a stringent risk assessment has been undertaken which shows that use of a toughened glass inner pane does not give any additional risk to those below rooflights. For further information please see Rooflight Association NTD14. By choosing a rooflight with a toughened inner pane, customers acknowledge and accept responsibility for the associated risks, including the need to carry out a satisfactory risk assessment, and are responsible for ensuring a rooflight with toughened inner pane is appropriate for the intended application, which is beyond the control of the rooflight manufacturer.


Fire Performance

Glass is designated Class A to EN13501-1, as it is included in the list of CWFT (classified without further test) materials published in the Official Journal of the EU (see European Commission Decision 96/603/EC).


These rooflights are glazed with a 4mm toughened outer pane and can therefore be regarded as having a BROOF(t4) classification as per English building regulations.

Roof Applications

Skyseal Roof Lantern rooflights are intended for installation onto a fully weathered and insulated builders upstand on flat and low pitch roofs. The surface of flat roofs normally require some degree of pitch to ensure adequate water runoff. For aesthetic reasons we recommend that the upstand is built with 0° pitch i.e. not parallel with the pitched roof surface. The rooflight can accommodate being installed on an upstand with a pitch of up to 5° but please note that this will likely result in a 'lopsided' appearance.



*Detail indicative of optional laminated inner pane




Sizes and Configurations

Roof Lantern	Roof Lantern Pyramid
1500 x 1000mm	1000 x 1000mm
2000 x 1000mm	1500 x 1500mm
2000 x 1500mm	2000 x 2500mm
2500 x 1000mm	2500 x 2500mm
2500 x 1500mm	
2500 x 2000mm	
3000 x 1000mm	
3000 x 1500mm	
3000 x 2000mm	


Standard stock units are supplied with 4 panes of glass as standard for a contemporary appearance.

An optional central rafter on the long side of the rooflight splits the larger glass pane in two, giving the rooflight a more traditional look.This option is also useful where site access is limited.


Bespoke sizes also available



4 pane option



6 pane option



4 pane pyramid

Skyseal Brighter Inside

www.skyseal.co.uk

TECHNICAL SUPPORT: For any technical information/queries please contact your supplier.

Skyseal operates a policy of continuous product improvement, and reserves the right to alter specifications at any time without notice. Every effort has been taken to ensure all details contained in this document are correct at the time of going to press but this document should be used only as a guide and does not in any way form part of a contract or warranty. It is the customer's responsibility to ensure that the product is suitable for the actual conditions of use, which are beyond the control of Skyseal.

Roof Lantern Roof Lantern Pyramid

TB432
Skyseal Roof Lantern Datasheet

Glazing Options and Performance

Available withclear/clearneutralself-clean or blue solar-control self-clean glass as standard. Other glazing options are available on request. If non-standard glass is used, glazing performance may differ from the table shown.

	Toughened Inner Pane		Laminated Inner Pane	
	Clear	Blue	Clear Neutral	Blue
Light Transmission (%)	77%	32%	44%	32%
Reflectance In / Out	16% / 16%	16% / 23%	21% / 25%	16% / 23%
G-Value	0.69	0.28	0.42	0.28
Shading Coefficient	0.79	0.33	0.48	0.32
Acoustic Performance (Rw) - Direct airborne sound insulation	33dB	33dB	37dB	37dB

Thermal Performance (England, Scotland and Wales)

There is currently no method set out for assessing the thermal performance of lantern rooflights, so the method shown in Rooflight Association (formerly NARM) NTD2 has been adopted as the most appropriate. The thermal transmittance values (assessed horizontally) are shown in the table.

Thermal Performance (England, Scotland and Wales)			
Width (mm)	Length (mm)	Surface:area ratio	U_r value (W/m^2K)
1000	1000	2.49	1.88
1000	1500	1.93	2.03
1000	2000	1.82	2.00
1000	2500	1.76	1.97
1000	3000	1.72	1.96
1500	1500	1.95	1.84
1500	2000	1.63	1.96
1500	2500	1.57	1.93
1500	3000	1.54	1.91
2000	2000	1.72	1.81
2000	2500	1.49	1.91
2000	3000	1.45	1.89
2500	2500	1.60	1.80

*The overall thermal performance of rooflights is still referredto as a U_d-value in the building regulations, rather than U_r/U_{rc} value as per the calculation method. Values stated are therefore equivalent to a U_d-value assessed horizontally.

Thermal Performance (Republic of Ireland,Northern Ireland)		
Width (mm)	Length (mm)	U_d value (W/m^2K)
1000	1000	1.62
1000	1500	1.72
1000	2000	1.67
1000	2500	1.64
1000	3000	1.61
1500	1500	1.51
1500	2000	1.59
1500	2500	1.55
1500	3000	1.53
2000	2000	1.44
2000	2500	1.51
2000	3000	1.49
2500	2500	1.40

Thermal Performance (Republic of Ireland and Northern Ireland)

The thermal performance of Roof Lantern is assessed in the vertical plane and depending on configuration achieves a U_d value as declared in the table shown. (The glazing used in Roof Lantern Glass achieves a centre pane U value of 1.2W/m²K).

TECHNICAL SUPPORT: For any technical information/queries please contact your supplier.

Skyseal operates a policy of continuous product improvement, and reserves the right to alter specifications at any time without notice. Every effort has been taken to ensure all details contained in this document are correct at the time of going to press but this document should be used only as a guide and does not in any way form part of a contract or warranty. It is the customer's responsibility to ensure that the product is suitable for the actual conditions of use, which are beyond the control of Skyseal.

Roof Lantern Roof Lantern Pyramid

TB432

Skyseal Roof Lantern Datasheet

Wind and Snow Loads

Skyseal Roof Lantern has been tested to show that, when correctly fitted in accordance with our instructions, will resist wind loads calculated in accordance with BS EN 1991-1-4: 2005, and imposed loads in accordance with BS EN 1873: 2005.

All sizes of Skyseal Roof Lantern can resist a snow load of 1200N/m^2.

Resistance to Wind Loads (upwards) N/m^2

Width (mm) \ Length (mm)	1000	1250	1500	1750	2000	2250	2500	2750	3000
1000	2400	2400	2400	2400	2400	2400	2400	2400	2400
1250	-	2400	2400	2400	2400	2400	2400	2400	2400
1500	-	-	2400	2400	2400	2400	2400	2400	2400
1750	-	-	-	2400	2400	2400	2400	2400	2400
2000	-	-	-	-	2400	2400	2400	2400	2400
2250	-	-	-	-	-	1200	1200	-	-
2500	-	-	-	-	-	-	1200	-	-

Product Height & Weight

Product Overall Height & Weight

Width (mm)	Length (mm)	Height (mm)	Laminated Inner Pane		Toughened Inner Pane	
			4 pane weight (kg)	6 pane weight (kg)	4 pane weight (kg)	6 pane weight (kg)
1000	1000	355	50	-	43	-
1000	1500	347	71	73	60	63
1000	2000	347	89	92	75	78
1000	2500	347	107	110	90	93
1000	3000	347	126	128	105	108
1500	1500	471	94	-	79	-
1500	2000	463	122	126	102	106
1500	2500	463	148	152	123	127
1500	3000	463	173	177	143	147
2000	2000	588	153	-	126	-
2000	2500	580	189	193	155	160
2000	3000	580	221	226	181	186
2500	2500	685	226	-	184	-

Bespoke sizes available on request.

Installation, Handling, Maintenance & Storage

Full installation details, maintenance and product care details are available on request.

TECHNICAL SUPPORT: For any technical information/queries please contact your supplier.

Skyseal operates a policy of continuous product improvement, and reserves the right to alter specifications at any time without notice. Every effort has been taken to ensure all details contained in this document are correct at the time of going to press but this document should be used only as a guide and does not in any way form part of a contract or warranty. It is the customer's responsibility to ensure that the product is suitable for the actual conditions of use, which are beyond the control of Skyseal.